


Tapered roller bearing 08125-08231-JTEKT - 08125-08231-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/08125-08231-jtekt>

Single-row tapered roller bearings inch series **Koyo**



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
d	D	T	B	C	r_a max.	r_b min.	C_r	C_{10}	Grease lub.	Oil lub.
31.750	58.738	14.684	15.080	10.716	1.0	1.0	29.5	33.3	6 600	8 900

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer to) Mass (kg)	
Inner ring	Outer ring	a	d_a	d_b	D_a	D_b	r_s max.	r_t max.	e	Y_1	Y_2	Inner ring	Outer ring
08125	08231	13.5	37.5	36.0	52.0	55.0	1.0	1.0	0.48	1.26	0.69	0.109	0.056

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952426044
Inside diameter	31.75 mm
Outside diameter	58.738 mm
Thickness	14.684 mm
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE