

Tapered roller bearing 02878-02820-JTEKT - 02878-02820-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/02878-02820-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
d	D	T	B	C	r_1 max.	r_1 min.	C_r	C_{10}	Grease lub.	Oil lub.
34.925	73.025	22.225	22.225	17.462	0.8	3.2	55.0	65.7	5 500	7 400

Bearing No.		Load center (mm)	Mounting dimensions (mm)					Constant	Axial load factors		(Refer to) Mass (kg)		
Inner ring	Outer ring	a	d_a	d_b	D_a	D_b	r_a max.	r_b max.	e	Y_1	Y_2	Inner ring	Outer ring
02878	02820	18.4	42.5	42.0	62.0	68.0	0.8	3.2	0.45	1.32	0.73	0.265	0.158

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952426334
Inside diameter	34.925 mm
Outside diameter	43.025 mm
Thickness	22.225 mm
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE