

Tapered roller bearing 449-432-JTEKT - 449-432-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/449-432-jtekt>

Single-row tapered roller bearings
Inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
d	D	T	B	C	r_a max.	r_b max.	C_r	C_{10}	Grease lub.	Oil lub.
34.925	95.250	27.783	29.901	22.225	0.8	2.4	103	122	4 500	5 900

Bearing No.		Load center (mm)	Mounting dimensions (mm)					Constant	Axial load factors		(Refer to Mass (kg))		
Inner ring	Outer ring	a	d_a	d_b	D_a	D_b	r_a max.	r_b max.	e	Y_1	Y_2	Inner ring	Outer ring
449	432	18.4	44.0	43.5	83.0	87.0	0.8	2.4	0.28	2.11	1.16	0.686	0.384

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952426396
Inside diameter	34.925 mm
Outside diameter	95.25 mm
Thickness	27.783 mm
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE