

Tapered roller bearing 2794R-2735X-JTEKT - 2794R-2735X-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/2794r-2735x-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r_a</i> max.	<i>r_b</i> max.	<i>C_r</i>	<i>C₁₀</i>	Grease lub.	Oil lub.
36.487	73.025	23.812	25.694	19.060	3.6	0.8	74.1	92.2	5 400	7 200

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer) Mass (kg)	
Inner ring	Outer ring	<i>a</i>	<i>d_a</i>	<i>d_b</i>	<i>D_a</i>	<i>D_b</i>	<i>r_a</i> max.	<i>r_b</i> max.	<i>e</i>	<i>Y₁</i>	<i>Y₂</i>	Inner ring	Outer ring
2794R	2735X	15.9	49.0	42.5	66.0	69.0	3.6	0.8	0.30	1.98	1.09	0.344	0.134

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952426457
Inside diameter	36.487 mm
Inside diameter	1.436" inch
Outside diameter	73.025 mm
Outside diameter	2 7/8" inch
Thickness	23.812 mm
Thickness	15/16" inch
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE