

Tapered roller bearing 2788R-2735X-JTEKT - 2788R-2735X-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/2788r-2735x-jtekt>

Single-row tapered roller bearings
inch series

Koyo

100mm series

Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> _{1 max}	<i>r</i> _{2 max}	<i>C</i> ₀	<i>C</i> ₁₀	Grease lub.	Oil lub.
38.100	73.025	23.812	25.664	19.050	3.6	0.8	74.1	92.2	5 400	7 200

Bearing No.		Load center (mm) <i>a</i>	Mounting dimensions (mm)						Constant <i>e</i>	Axial load factor		(Refer) Mass (kg)	
Inner ring	Outer ring		<i>d</i> _s	<i>d</i> _b	<i>D</i> _s	<i>D</i> _b	<i>r</i> _{s max}	<i>r</i> _{b max}		<i>Y</i> ₁	<i>Y</i> ₂	Inner ring	Outer ring
2788R	2735X	15.9	50.0	43.5	66.0	69.0	3.6	0.8	0.30	1.98	1.09	0.308	0.134

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952426600
Inside diameter	38.1 mm
Outside diameter	73.025 mm
Thickness	23.812 mm
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE