


## Tapered roller bearing 27880-27820-JTEKT - 27880-27820-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/27880-27820-jtekt>

Single-row tapered roller bearings inch series Koyo



Boundary dimensions (mm)								Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> <sub>a</sub>	<i>r</i> <sub>b</sub>	<i>r</i> <sub>s</sub>	<i>C</i> <sub>r</sub>	<i>C</i> <sub>10</sub>	Grease lub.	Oil lub.
<b>38.100</b>	80.035	24.608	23.698	18.912	0.8	1.6		73.2	91.6	5 200	6 900

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer to)	
Inner ring	Outer ring	<i>a</i>	<i>d</i> <sub>a</sub>	<i>d</i> <sub>b</sub>	<i>D</i> <sub>a</sub>	<i>D</i> <sub>b</sub>	<i>r</i> <sub>a</sub> max.	<i>r</i> <sub>b</sub> max.	<i>e</i>	<i>Y</i> <sub>1</sub>	<i>Y</i> <sub>2</sub>	Inner ring	Outer ring
<b>27880</b>	<b>27820</b>	22.2	48.0	47.0	68.0	75.0	0.8	1.6	0.56	1.07	0.59	0.378	0.208

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952426631
Inside diameter	38.1 mm
Outside diameter	80.035 mm
Thickness	24.608 mm
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE