

Tapered roller bearing 18587-18520-JTEKT - 18587-18520-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/18587-18520-jtekt>

Single-row tapered roller bearings
inch series **Koyo**

Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> _{min}	<i>r</i> _{max}	<i>C</i> _r	<i>C</i> _{0r}	Grease lub.	Oil lub.
39.688	73.025	16.667	17.462	12.700	0.8	1.6	45.9	55.8	5 200	6 900

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring	<i>a</i>	<i>d</i> _a	<i>d</i> _b	<i>D</i> _a	<i>D</i> _b	<i>r</i> _{max}	<i>r</i> _{min}	<i>e</i>	<i>Y</i> ₁	<i>Y</i> ₂	Inner ring	Outer ring
18587	18520	14.5	46.0	46.0	66.0	68.0	0.8	1.6	0.35	1.71	0.94	0.215	0.085

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952426693
Inside diameter	39.688 mm
Outside diameter	73.025 mm
Thickness	16.667 mm
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE