

Tapered roller bearing 28158-28300-JTEKT - 28158-28300-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/28158-28300-jtekt>

Single-row tapered roller bearings Koyo
inch series



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> ₁ max.	<i>r</i> ₁ min.	<i>C</i> _r	<i>C</i> _{10v}	Grease lub.	Oil lub.
40.000	76.200	20.638	20.940	19.607	1.6	1.2	57.3	65.9	5 300	7 000

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer to)	
Inner ring	Outer ring	<i>a</i>	<i>d</i> _a	<i>d</i> _b	<i>D</i> _a	<i>D</i> _b	<i>r</i> _a max.	<i>r</i> _b max.	<i>e</i>	<i>Y</i> ₁	<i>Y</i> ₂	Inner ring	Outer ring
28158	28300	16.5	47.5	45.0	68.0	71.0	1.6	1.2	0.40	1.49	0.82	0.266	0.137

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250107252
Inside diameter	40 mm
Outside diameter	76.2 mm
Thickness	20.638 mm
Weight	412 g
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE