


Tapered roller bearing 420-414-JTEKT - 420-414-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/420-414-jtekt>

Single-row tapered roller bearings Koyo
inch series



| Boundary dimensions (mm) | | | | | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | |
|--------------------------|--------|--------|--------|--------|------------------------|------------------------|-------------------------|-----------------|--------------------------------------|----------|
| d | D | T | B | C | r ₁ max. | r ₁ min. | C _r | C ₁₀ | Grease lub. | Oil lub. |
| 40.000 | 88.501 | 26.988 | 29.083 | 22.225 | 3.6 | 1.6 | 98.2 | 112 | 4 900 | 6 500 |

| Bearing No. | | Load center (mm) | Mounting dimensions (mm) | | | | | | Con-stant | Axial load factors | | (Refer.) Mass (kg) | |
|-------------|------------|------------------|--------------------------|----------------|----------------|----------------|------------------------|------------------------|-----------|--------------------|----------------|--------------------|------------|
| Inner ring | Outer ring | a | d _a | d _b | D _a | D _b | r _a max. | r _b max. | e | Y ₁ | Y ₂ | Inner ring | Outer ring |
| 420 | 414 | 16.9 | 52.0 | 46.0 | 77.0 | 80.0 | 3.6 | 1.6 | 0.26 | 2.28 | 1.25 | 0.465 | 0.325 |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | JTEKT |
| N° Ean13 | 3663952426792 |
| Inside diameter | 40 mm |
| Inside diameter | 1.575" inch |
| Outside diameter | 88.501 mm |
| Outside diameter | 3.484" inch |
| Thickness | 26.988 mm |
| Thickness | 1 1/16" inch |
| Packaging | 1 |

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE