

## Tapered roller bearing 46162-46368-JTEKT - 46162-46368-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/46162-46368-jtekt>

Single-row tapered roller bearings ————— **Koyo**  
inch series



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
$d$	$D$	$T$	$B$	$C$	$r_a$ max.	$r_b$ max.	$C_r$	$C_{10}$	Grease lub.	Oil lub.
41.275	93.662	31.750	31.750	26.195	0.8	3.2	105	134	4 400	5 800

  

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer to)	
Inner ring	Outer ring	$a$	$d_a$	$d_b$	$D_a$	$D_b$	$r_a$ max.	$r_b$ max.	$e$	$Y_1$	$Y_2$	Inner ring	Outer ring
46162	46368	24.0	52.0	51.0	79.0	87.0	0.8	3.2	0.40	1.49	0.82	0.695	0.403

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952426921
Inside diameter	41.275 mm
Outside diameter	93.662 mm
Thickness	31.75 mm
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE