

Tapered roller bearing HM804840-HM804810-JTEKT - HM804840-HM804810-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/hm804840-hm804810-jtekt>

Single-row tapered roller bearings — Koyo
Inch series



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
d	D	T	B	C	r_1 max.	r_2 min.	C_r	C_{10}	Grease lub.	Oil lub.
41.275	95.250	30.162	29.370	23.020	3.6	3.2	104	140	3 300	4 400

Bearing No.		Load center (mm)	Mounting dimensions (mm)					Constant	Axial load factors		(Refer to Mass (kg))		
Inner ring	Outer ring	a	d_a	d_b	D_a	D_b	r_a max.	r_b max.	e	Y_1	Y_2	Inner ring	Outer ring
HM804840	HM804810	26.5	61.0	54.0	81.0	91.0	3.6	3.2	0.55	1.10	0.60	0.719	0.351

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952426938
Inside diameter	41.275 mm
Outside diameter	95.25 mm
Thickness	30.162 mm
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE