

Tapered roller bearing 18685-18620-JTEKT - 18685-18620-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/18685-18620-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r_a</i>	<i>r_b</i>	<i>C_r</i>	<i>C₁₀</i>	Grease lub.	Oil lub.
44.450	79.375	17.462	17.462	12.495	2.8	1.6	47.1	59.1	4 800	6 400

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer to)	
Inner ring	Outer ring	<i>a</i>	<i>d_a</i>	<i>d_b</i>	<i>D_a</i>	<i>D_b</i>	<i>r_a</i> max.	<i>r_b</i> max.	<i>e</i>	<i>Y₁</i>	<i>Y₂</i>	Inner ring	Outer ring
18685	18620	16.0	54.0	49.5	71.0	74.0	2.8	1.6	0.37	1.60	0.88	0.214	0.126

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952427034
Inside diameter	44.45 mm
Outside diameter	79.375 mm
Thickness	17.462 mm
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE