

Tapered roller bearing 615-612-JTEKT - 615-612-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/615-612-jtekt>

Single-row tapered roller bearings Koyo
inch series



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
d	D	T	B	C	r ₁	r ₂	C _r	C ₁₀	Grease lub.	Oil lub.
44.450	120.650	41.275	41.275	31.760	3.6	3.2	174	217	3 500	4 600

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring	a	d _a	d _b	D _a	D _b	r _a max.	r _b max.	e	Y ₁	Y ₂	Inner ring	Outer ring
615	612	27.3	62.0	56.0	105.0	110.0	3.6	3.2	0.31	1.91	1.05	1.48	0.853

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952427195
Inside diameter	44.45 mm
Inside diameter	1 3/4" inch
Outside diameter	120.65 mm
Outside diameter	4 3/4" inch
Thickness	41.275 mm
Thickness	1 5/8" inch
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE