

## Tapered roller bearing 467-453X-JTEKT - 467-453X-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/467-453x-jtekt>

Single-row tapered roller bearings ————— **Koyo**  
inch series



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
d	D	T	B	C	r <sub>1</sub> max.	r <sub>1</sub> min.	C <sub>r</sub>	C <sub>10</sub>	Grease lub.	Oil lub.
47.625	104.775	30.162	29.317	24.605	0.8	3.2	109	144	3 700	4 900

  

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring	a	d <sub>a</sub>	d <sub>b</sub>	D <sub>a</sub>	D <sub>b</sub>	r <sub>a</sub> max.	r <sub>b</sub> max.	e	Y <sub>1</sub>	Y <sub>2</sub>	Inner ring	Outer ring
467	453X	23.6	57.0	56.0	92.0	98.0	0.8	3.2	0.34	1.79	0.98	0.844	0.372

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952427393
Inside diameter	47.625 mm
Inside diameter	1 7/8" inch
Outside diameter	104.775 mm
Outside diameter	4 1/8" inch
Thickness	30.162 mm
Thickness	1 3/16" inch
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE