


## Tapered roller bearing 45282-45220-JTEKT - 45282-45220-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/45282-45220-jtekt>

Single-row tapered roller bearings  
inch series **Koyo**



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r<sub>a</sub></i>	<i>r<sub>b</sub></i>	<i>C<sub>r</sub></i>	<i>C<sub>10</sub></i>	Grease lub.	Oil lub.
47.625	104.775	30.162	30.968	22.812	3.6	3.2	126	165	3 700	4 900

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		Mass (kg)	
Inner ring	Outer ring	<i>a</i>	<i>d<sub>a</sub></i>	<i>d<sub>b</sub></i>	<i>D<sub>a</sub></i>	<i>D<sub>b</sub></i>	<i>r<sub>a</sub></i> max.	<i>r<sub>b</sub></i> max.	<i>e</i>	<i>Y<sub>1</sub></i>	<i>Y<sub>2</sub></i>	Inner ring	Outer ring
45282	45220	22.2	64.0	59.0	93.0	99.0	3.6	3.2	0.33	1.80	0.99	0.940	0.345

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952427409
Inside diameter	47.625 mm
Outside diameter	104.775 mm
Thickness	30.162 mm
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE