

Tapered roller bearing 396-394A-JTEKT - 396-394A-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/396-394a-jtekt>

Single-row tapered roller bearings ————— **Koyo**
inch series



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
d	D	T	B	C	r ₁	r ₂	C _r	C ₁₀	Grease lub.	Oil lub.
50.000	110.000	22.000	21.986	18.824	0.8	1.2	86.4	116	3 400	4 500

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Con-stant	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring	a	d _a	d _b	D _a	D _b	r _a max.	r _b max.	e	Y ₁	Y ₂	Inner ring	Outer ring
396	394A	21.3	61.0	60.0	101.0	105.0	0.8	1.2	0.40	1.49	0.82	0.777	0.264

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952427621
Inside diameter	50 mm
Outside diameter	110 mm
Thickness	22 mm
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE