

Tapered roller bearing 39575-39520-JTEKT - 39575-39520-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/39575-39520-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
d	D	T	B	C	r_a max.	r_b max.	C_r	C_{10}	Grease lub.	Oil lub.
50.800	112.712	30.162	30.162	22.812	3.6	3.2	147	207	3 300	4 500

Bearing No.		Load center (mm)	Mounting dimensions (mm)					Constant	Axial load factors		Mass (kg)		
Inner ring	Outer ring	a	d_a	d_b	D_a	D_b	r_a max.	r_b max.	e	Y_1	Y_2	Inner ring	Outer ring
39575	39520	23.3	68.0	61.0	101.0	107.0	3.6	3.2	0.34	1.77	0.97	1.13	0.355

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952427799
Inside diameter	50.8 mm
Outside diameter	112.712 mm
Thickness	30.162 mm
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE