


Tapered roller bearing 468-453X-JTEKT - 468-453X-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/468-453x-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)						Basic load ratings (kN)		Limiting speeds (min ⁻¹)		
d	D	T	B	C	r ₁ max.	r ₁ min.	C _r	C ₁₀	Grease lub.	Oil lub.
52.388	104.775	30.162	29.317	24.805	1.6	3.2	109	144	3 700	4 900

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring	a	d _a	d _b	D _a	D _b	r _a max.	r _b max.	e	Y ₁	Y ₂	Inner ring	Outer ring
468	453X	23.6	62.0	60.0	92.0	98.0	1.6	3.2	0.34	1.79	0.98	0.748	0.372

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952427843
Inside diameter	52.388 mm
Inside diameter	2 1/16" inch
Outside diameter	104.775 mm
Outside diameter	4 1/8" inch
Thickness	30.162 mm
Thickness	1 3/16" inch
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE