

Tapered roller bearing 539A-532X-JTEKT - 539A-532X-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/539a-532x-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
d	D	T	B	C	r_a max.	r_b max.	C_r	C_{10}	Grease lub.	Oil lub.
53.975	107.950	36.512	36.967	28.575	5.6	3.2	138	172	3 800	5 100

Bearing No.		Load center (mm)	Mounting dimensions (mm)					Constant	Axial load factors		(Refer) Mass (kg)		
Inner ring	Outer ring	a	d_a	d_b	D_a	D_b	r_a max.	r_b max.	e	Y_1	Y_2	Inner ring	Outer ring
539A	532X	23.9	72.0	61.0	94.0	100.0	5.6	3.2	0.30	2.03	1.11	0.861	0.569

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952427898
Inside diameter	53.975 mm
Inside diameter	2 1/8" inch
Outside diameter	107.95 mm
Outside diameter	4 1/4" inch
Thickness	36.512 mm
Thickness	1 7/16" inch
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE