


## Tapered roller bearing 5584R-5535-JTEKT - 5584R-5535-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/5584r-5535-jtekt>

Single-row tapered roller bearings inch series Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r<sub>a</sub></i>	<i>r<sub>b</sub></i>	<i>C<sub>r</sub></i>	<i>C<sub>0r</sub></i>	Grease lub.	Oil lub.
63.500	122.238	43.658	43.764	36.612	3.6	3.2	221	318	3 200	4 300

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring	<i>a</i>	<i>d<sub>a</sub></i>	<i>d<sub>b</sub></i>	<i>D<sub>a</sub></i>	<i>D<sub>b</sub></i>	<i>r<sub>a</sub></i> max.	<i>r<sub>b</sub></i> max.	<i>e</i>	<i>Y<sub>1</sub></i>	<i>Y<sub>2</sub></i>	Inner ring	Outer ring
5584R	5535	31.1	61.0	75.0	106.0	116.0	3.6	3.2	0.36	1.67	0.92	1.56	0.807

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952428499
Inside diameter	63.5 mm
Outside diameter	122.238 mm
Thickness	43.658 mm
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE