

Tapered roller bearing HM212049-HM212010-JTEKT - HM212049-HM212010-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/hm212049-hm212010-jtekt>

Single-row tapered roller bearings — Koyo
inch series



Boundary dimensions (mm)							Basic load ratings (kN)			Limiting speeds (min ⁻¹)	
d	D	T	B	C	r ₁	r ₂	C _r	C ₁₀	Grease lub.	Oil lub.	
66.675	122.238	38.100	38.364	22.718	3.6	1.6	191	249	3 200	4 300	

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer) Mass (kg)	
Inner ring	Outer ring	a	d _a	d _b	D _a	D _b	r _a max.	r _b max.	e	Y ₁	Y ₂	Inner ring	Outer ring
HM212049	HM212010	27.3	82.0	75.5	110.0	116.0	3.6	1.6	0.34	1.78	0.98	1.26	0.596

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952428635
Inside diameter	66.675 mm
Outside diameter	122.238 mm
Thickness	38.1 mm
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE