


Tapered roller bearing 641-633-JTEKT - 641-633-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/641-633-jtekt>

Single-row tapered roller bearings Koyo
inch series



Boundary dimensions (mm)							Basic load ratings (kN)			Limiting speeds (min ⁻¹)	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> ₁ max.	<i>r</i> ₁ min.	<i>C</i> _r	<i>C</i> ₁₀	Grease lub.	Oil lub.	
66.675	130.175	41.275	41.275	31.760	3.6	3.2	197	267	3 000	3 900	

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring	<i>a</i>	<i>d</i> _a	<i>d</i> _b	<i>D</i> _a	<i>D</i> _b	<i>r</i> _a max.	<i>r</i> _b max.	<i>e</i>	<i>Y</i> ₁	<i>Y</i> ₂	Inner ring	Outer ring
641	633	30.3	83.0	77.0	116.0	124.0	3.6	3.2	0.36	1.66	0.91	1.68	0.703

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952428659
Inside diameter	66.675 mm
Outside diameter	130.175 mm
Thickness	41.275 mm
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE