


Tapered roller bearing 6389-6320-JTEKT - 6389-6320-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/6389-6320-jtekt>

Single-row tapered roller bearings inch series Koyo



Boundary dimensions (mm)								Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r_a</i>	<i>r_b</i>		<i>C_r</i>	<i>C₁₀</i>	Grease lub.	Oil lub.
66.675	135.755	53.975	56.007	44.450	6.4	3.2		266	357	3 000	4 000

Bearing No.		Load center (mm) <i>a</i>	Mounting dimensions (mm)						Constant <i>e</i>	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring		<i>d_a</i>	<i>d_b</i>	<i>D_a</i>	<i>D_b</i>	<i>r_a</i> max.	<i>r_b</i> max.		<i>Y₁</i>	<i>Y₂</i>	Inner ring	Outer ring
6389	6320	34.8	91.0	77.5	117.0	126.0	6.4	3.2	0.32	1.85	1.02	2.15	1.37

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952428673
Inside diameter	66.675 mm
Inside diameter	2 5/8" inch
Outside diameter	135.755 mm
Outside diameter	5.345" inch
Thickness	53.975 mm
Thickness	2 1/8" inch
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE