


Tapered roller bearing

H414242-H414210-JTEKT - H414242-H414210-JTEKT

https://www.123bearing.com/bearing-housing/roller-bearing/tapered/h414242-h414210-jtekt

Single-row tapered roller bearings ————— **Koyo**
inch series



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
d	D	T	B	C	r ₁	r ₂	C _r	C ₁₀	Grease lub.	Oil lub.
66.675	136.525	41.275	41.275	31.760	3.6	3.2	241	308	2 900	3 800

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer)	
Inner ring	Outer ring	a	d _a	d _b	D _a	D _b	r _a max.	r _b max.	e	Y ₁	Y ₂	Inner ring	Outer ring
H414242	H414210	30.3	85.0	81.0	121.0	129.0	3.6	3.2	0.36	1.67	0.92	2.01	0.796

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952428680
Inside diameter	66.675 mm
Outside diameter	136.525 mm
Thickness	41.275 mm
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE