

Tapered roller bearing 482-472X-JTEKT - 482-472X-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/482-472x-jtekt>

Single-row tapered roller bearings
inch series

Koyo



| Boundary dimensions (mm) | | | | | | | Basic load ratings (kN) | | | Limiting speeds (min ⁻¹) | |
|--------------------------|---------|--------|--------|--------|------------------------|------------------------|-------------------------|-----------------|-------------|--------------------------------------|--|
| d | D | T | B | C | r ₁ max. | r ₁ min. | C _r | C ₁₀ | Grease lub. | Oil lub. | |
| 69.850 | 123.825 | 30.162 | 29.007 | 24.605 | 3.6 | 3.2 | 118 | 161 | 3 200 | 4 200 | |

| Bearing No. | | Load center (mm) | Mounting dimensions (mm) | | | | | | Constant | Axial load factors | | (Refer to) | |
|-------------|------------|------------------|--------------------------|----------------|----------------|----------------|------------------------|------------------------|----------|--------------------|----------------|------------|------------|
| Inner ring | Outer ring | a | d _a | d _b | D _a | D _b | r _a max. | r _b max. | e | Y ₁ | Y ₂ | Inner ring | Outer ring |
| 482 | 472X | 26.0 | 83.0 | 77.0 | 109.0 | 114.0 | 3.6 | 3.2 | 0.38 | 1.56 | 0.86 | 0.791 | 0.625 |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | JTEKT |
| N° Ean13 | 3663952428833 |
| Inside diameter | 69.85 mm |
| Outside diameter | 123.825 mm |
| Thickness | 30.162 mm |
| Packaging | 1 |

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE