

Tapered roller bearing HH221430-HH221410-JTEKT - HH221430-HH221410-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/hh221430-hh221410-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)			Limiting speeds (min ⁻¹)	
d	D	T	B	C	r ₁	r ₂	C _r	C ₁₀	Grease lub.	Oil lub.	
76.200	190.500	57.150	57.531	40.038	3.6	3.2	440	602	2 000	2 700	

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer) Mass (kg)	
Inner ring	Outer ring	a	d _a	d _b	D _a	D _b	r _a max.	r _b max.	e	Y ₁	Y ₂	Inner ring	Outer ring
HH221430	HH221410	42.5	101.0	95.0	171.0	179.0	3.6	3.2	0.33	1.79	0.99	6.33	2.21

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952429199
Inside diameter	76.2 mm
Outside diameter	190.5 mm
Thickness	57.15 mm
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE