


Tapered roller bearing 756A-752-JTEKT - 756A-752-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/756a-752-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)			Limiting speeds (min ⁻¹)	
d	D	T	B	C	r ₁	r ₂	C _r	C ₁₀	Grease lub.	Oil lub.	
79.375	161.925	47.625	48.260	38.100	7.9	3.2	273	391	2 400	3 200	

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring	a	d _a	d _b	D _a	D _b	r _a max.	r _b max.	e	Y ₁	Y ₂	Inner ring	Outer ring
756A	752	35.5	106.0	91.0	144.0	150.0	7.9	3.2	0.34	1.76	0.97	2.95	1.59

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952429267
Inside diameter	79.375 mm
Inside diameter	3 1/8" inch
Outside diameter	161.925 mm
Outside diameter	6 3/8" inch
Thickness	47.625 mm
Thickness	1 7/8" inch
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE