


Tapered roller bearing 750AR-742-JTEKT - 750AR-742-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/750ar-742-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
d	D	T	B	C	r_{max}	r_{min}	C_r	C_{10}	Grease lub.	Oil lub.
82.550	150.089	44.450	46.672	30.512	6.7	3.2	264	368	2 500	3 400

Bearing No.		Load center (mm) a	Mounting dimensions (mm)						Constant e	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring		d_s	d_b	D_s	D_b	$r_{s \text{ max}}$	$r_{b \text{ max}}$		Y_1	Y_2	Inner ring	Outer ring
750AR	742	32.4	106.0	93.0	134.0	142.0	6.7	3.2	0.33	1.84	1.01	2.19	1.06

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952429397
Inside diameter	82.55 mm
Outside diameter	150.089 mm
Thickness	44.45 mm
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE