

Tapered roller bearing L217849-L217810-JTEKT - L217849-L217810-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/l217849-l217810-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
d	D	T	B	C	r_a max.	r_b max.	C_r	C_{10}	Grease lub.	Oil lub.
88.900	123.825	20.638	20.638	10.670	1.6	1.6	81.8	145	2 800	3 700

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer) Mass (kg)	
Inner ring	Outer ring	a	d_a	d_b	D_a	D_b	r_a max.	r_b max.	e	Y_1	Y_2	Inner ring	Outer ring
L217849	L217810	20.7	97.0	94.0	116.0	119.0	1.6	1.6	0.33	1.82	1.00	0.507	0.235

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952429588
Inside diameter	88.9 mm
Inside diameter	3 1/2" inch
Outside diameter	123.825 mm
Outside diameter	4 7/8" inch
Thickness	20.638 mm
Thickness	13/16" inch
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE