

Tapered roller bearing 679-672-JTEKT - 679-672-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/679-672-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
d	D	T	B	C	r ₁ max.	r ₁ min.	C _r	C ₁₀	Grease lub.	Oil lub.
88.900	168.275	41.275	41.275	30.162	3.6	3.2	224	349	2 200	3 000

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring	a	d _a	d _b	D _a	D _b	r _a max.	r _b max.	e	Y ₁	Y ₂	Inner ring	Outer ring
679	672	38.6	107.0	101.0	149.0	160.0	3.6	3.2	0.47	1.28	0.70	2.75	1.22

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952429625
Inside diameter	88.9 mm
Outside diameter	168.275 mm
Thickness	41.275 mm
Packaging	-

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE