

Tapered roller bearing 778-772-JTEKT - 778-772-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/778-772-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
d	D	T	B	C	r ₁ max.	r ₁ min.	C _r	C ₁₀	Grease lub.	Oil lub.
92.075	180.975	47.625	48.006	38.100	3.6	3.2	288	438	2 100	2 800

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer to)	
Inner ring	Outer ring	a	d _a	d _b	D _a	D _b	r _a max.	r _b max.	e	Y ₁	Y ₂	Inner ring	Outer ring
778	772	39.5	111.0	105.0	161.0	168.0	3.6	3.2	0.39	1.56	0.86	3.65	1.92

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952429779
Inside diameter	92.075 mm
Outside diameter	180.975 mm
Thickness	47.625 mm
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE