

Tapered roller bearing LL319349-LL319310-JTEKT - LL319349-LL319310-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/ll319349-ll319310-jtekt>

Single-row tapered roller bearings
inch series

Koyo



| Boundary dimensions (mm) | | | | | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | |
|--------------------------|----------|----------|----------|----------|-------------------------------|-------------------------------|-------------------------|------------------------|--------------------------------------|----------|
| <i>d</i> | <i>D</i> | <i>T</i> | <i>B</i> | <i>C</i> | <i>r</i> _a max. | <i>r</i> _b max. | <i>C</i> _r | <i>C</i> ₁₀ | Grease lub. | Oil lub. |
| 95.250 | 128.588 | 15.875 | 15.083 | 11.908 | 1.6 | 1.6 | 58.0 | 93.0 | 2 600 | 3 500 |

| Bearing No. | | Load center (mm) | Mounting dimensions (mm) | | | | | Constant | Axial load factors | | (Refer to) | | |
|-------------|------------|------------------|--------------------------|-----------------------|-----------------------|-----------------------|-------------------------------|-------------------------------|--------------------|-----------------------|-----------------------|------------|------------|
| Inner ring | Outer ring | <i>a</i> | <i>d</i> _a | <i>d</i> _b | <i>D</i> _a | <i>D</i> _b | <i>r</i> _a max. | <i>r</i> _b max. | <i>e</i> | <i>Y</i> ₁ | <i>Y</i> ₂ | Inner ring | Outer ring |
| LL319349 | LL319310 | 20.3 | 103.0 | 100.0 | 122.0 | 124.0 | 1.6 | 1.6 | 0.35 | 1.71 | 0.94 | 0.390 | 0.147 |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | JTEKT |
| N° Ean13 | 3663952429793 |
| Inside diameter | 95.25 mm |
| Outside diameter | 128.588 mm |
| Thickness | 15.875 mm |
| Packaging | 1 |

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE