

# Tapered roller bearing HH221440-HH221410-JTEKT - HH221440-HH221410-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/hh221440-hh221410-jtekt>

Single-row tapered roller bearings  
inch series

Koyo



Boundary dimensions (mm)								Basic load ratings (kN)			Limiting speeds (min <sup>-1</sup> )	
d	D	T	B	C	r <sub>1</sub>	r <sub>2</sub>	r <sub>3</sub>	C <sub>r</sub>	C <sub>10</sub>	Grease lub.	Oil lub.	
95.250	190.500	57.150	57.531	46.038	7.9	3.2		440	602	2 000	2 700	

  

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer) Mass (kg)	
Inner ring	Outer ring	a	d <sub>a</sub>	d <sub>b</sub>	D <sub>a</sub>	D <sub>b</sub>	r <sub>a</sub> max.	r <sub>b</sub> max.	e	Y <sub>1</sub>	Y <sub>2</sub>	Inner ring	Outer ring
HH221440	HH221410	42.5	125.0	110.0	171.0	179.0	7.9	3.2	0.33	1.79	0.99	5.16	2.21

## PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952429861
Inside diameter	95.25 mm
Outside diameter	190.5 mm
Thickness	57.15 mm
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE