


Tapered roller bearing 98400-98788-JTEKT - 98400-98788-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/98400-98788-jtekt>

Single-row tapered roller bearings
inch series

Koyo



| Boundary dimensions (mm) | | | | | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | |
|--------------------------|----------|----------|----------|----------|------------------------------|------------------------------|-------------------------|-----------------------|--------------------------------------|----------|
| <i>d</i> | <i>D</i> | <i>T</i> | <i>B</i> | <i>C</i> | <i>r_a</i> max. | <i>r_b</i> min. | <i>C_r</i> | <i>C₁₀</i> | Grease lub. | Oil lub. |
| 101.600 | 200.000 | 52.761 | 49.212 | 34.925 | 3.6 | 3.2 | 347 | 471 | 1 400 | 1 900 |

| Bearing No. | | Load center (mm) | Mounting dimensions (mm) | | | | | | Constant | Axial load factors | | (Refer.) Mass (kg) | |
|-------------|------------|------------------|--------------------------|----------------------|----------------------|----------------------|------------------------------|------------------------------|----------|----------------------|----------------------|--------------------|------------|
| Inner ring | Outer ring | <i>a</i> | <i>d_a</i> | <i>d_b</i> | <i>D_a</i> | <i>D_b</i> | <i>r_a</i> max. | <i>r_b</i> max. | <i>e</i> | <i>Y₁</i> | <i>Y₂</i> | Inner ring | Outer ring |
| 98400 | 98788 | 54.5 | 114.0 | 123.0 | 170.0 | 185.0 | 3.6 | 3.2 | 0.83 | 0.95 | 0.52 | 4.55 | 2.28 |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | JTEKT |
| N° Ean13 | 3663952429984 |
| Inside diameter | 101.6 mm |
| Inside diameter | 4" inch |
| Outside diameter | 200 mm |
| Outside diameter | 7.874" inch |
| Thickness | 52.761 mm |
| Thickness | 2.077" inch |
| Weight | 7020 g |
| Packaging | 1 |
| Standard | No standard |

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE