

Tapered roller bearing 56418R-56650-JTEKT - 56418R-56650-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/56418r-56650-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
d	D	T	B	C	r ₁ max.	r ₁ min.	C _r	C ₁₀	Grease lub.	Oil lub.
106.362	165.100	36.512	36.512	20.988	3.6	3.2	195	325	2 200	2 900

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer to)	
Inner ring	Outer ring	a	d _a	d _b	D _a	D _b	r _a max.	r _b max.	e	Y ₁	Y ₂	Inner ring	Outer ring
56418R	56650	38.6	122.0	116.0	149.0	159.0	3.6	3.2	0.50	1.21	0.66	1.84	0.852

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952430058
Inside diameter	106.362 mm
Outside diameter	165.1 mm
Thickness	36.512 mm
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE