

Tapered roller bearing 56425R-56662-JTEKT - 56425R-56662-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/56425r-56662-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)								Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
d	D	T	B	C	r ₁	r ₂	r ₃	C _r	C ₁₀	Grease lub.	Oil lub.
107.950	168.275	36.512	36.512	20.988	3.6	3.2		195	325	2 200	2 900

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer to)	
Inner ring	Outer ring	a	d _a	d _b	D _a	D _b	r _a max.	r _b max.	e	Y ₁	Y ₂	Inner ring	Outer ring
56425R	56662	38.6	123.0	117.0	150.0	160.0	3.6	3.2	0.50	1.21	0.66	1.76	1.03

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952430102
Inside diameter	107.95 mm
Outside diameter	168.275 mm
Thickness	36.512 mm
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE