

# Tapered roller bearing HH228340-HH228310-JTEKT - HH228340-HH228310-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/hh228340-hh228310-jtekt>

Single-row tapered roller bearings  
inch series

Koyo



Boundary dimensions (mm)								Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
d	D	T	B	C	r <sub>1</sub> max.	r <sub>1</sub> min.	C <sub>r</sub>	C <sub>10</sub>	Grease lub.	Oil lub.	
120.650	254.000	77.788	82.560	61.912	9.5	6.4	717	1 050	1 500	2 000	

  

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Con-stant	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring	a	d <sub>a</sub>	d <sub>b</sub>	D <sub>a</sub>	D <sub>b</sub>	r <sub>a</sub> max.	r <sub>b</sub> max.	e	Y <sub>1</sub>	Y <sub>2</sub>	Inner ring	Outer ring
HH228340	HH228310	54.3	158.0	142.0	223.0	234.0	9.5	6.4	0.32	1.87	1.03	12.6	6.00

## PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952430478
Inside diameter	120.65 mm
Outside diameter	254 mm
Thickness	77.788 mm
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE