

# Tapered roller bearing LM245848-LM245810-JTEKT - LM245848-LM245810-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/lm245848-lm245810-jtekt>

Single-row tapered roller bearings  
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)			Limiting speeds (min <sup>-1</sup> )	
$d$	$D$	$T$	$B$	$C$	$r_a$	$r_b$	$C_r$	$C_{10}$	Grease lub. Oil lub.		
231.775	317.500	47.625	52.388	30.513	3.2	3.2	488	928	970	1 300	

  

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer)	
Inner ring	Outer ring	$a$	$d_a$	$d_b$	$D_a$	$D_b$	$r_a$ max.	$r_b$ max.	$e$	$Y_1$	$Y_2$	Inner ring	Outer ring
LM245848	LM245810	50.5	244.0	240.0	309.0	312.0	3.2	3.2	0.33	1.80	0.99	8.02	2.78

## PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952431826
Inside diameter	231.775 mm
Outside diameter	317.5 mm
Thickness	47.625 mm
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE