

Tapered roller bearing M249749-M249710-JTEKT - M249749-M249710-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/m249749-m249710-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
d	D	T	B	C	r_a max.	r_b max.	C_r	C_{10}	Grease lub.	Oil lub.
254.000	358.775	71.438	71.438	53.975	3.6	3.2	773	1 590	840	1 100

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer)	
Inner ring	Outer ring	a	d_a	d_b	D_a	D_b	r_a max.	r_b max.	e	Y_1	Y_2	Inner ring	Outer ring
M249749	M249710	64.4	268.0	279.0	330.0	342.0	3.6	3.2	0.33	1.80	0.99	14.8	6.44

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952431864
Inside diameter	254 mm
Outside diameter	358.775 mm
Thickness	71.438 mm
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE