

## Needle roller bearing BHTM1020-JTEKT - BHTM1020-JTEKT

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/needle/bhtm1020-jtekt>

Drawn cup needle roller bearings Koyo



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	Bearing No. <sup>2)</sup>
$F_w$	$D$	$C$	$b$ min.	$C_r$	$C_{0r}$	Oil lub.	Caged type With open ends    With closed end
10	17	20	17.3	10.7	12.5	30 000	<b>BHTM1020</b>

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (φ6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	9.991	10.000	16.977	16.995	16	18

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952469621
Inside diameter	10 mm
Outside diameter	17 mm
Thickness	20 mm
Weight	16 g
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE