

Needle roller bearing BHTM1616A-JTEKT - BHTM1616A-JTEKT

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/needle/bhtm1616a-jtekt>

Drawn cup needle roller bearings Koyo



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min ⁻¹)	Bearing No. ²⁾
F _w	D	C	b min.	C ₀	C ₁₀	Oil lub.	Caged type With open ends With closed end
16	24	16	13.3	12.2	14.9	21 000	BHTM1616A

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (φ6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	15.989	16.000	23.991 ⁴⁾	24.012 ⁴⁾	20	23

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952470368
Inside diameter	16 mm
Inside diameter	0.63" inch
Outside diameter	24 mm
Outside diameter	0.945" inch
Thickness	16 mm
Thickness	0.63" inch
Weight	20 g
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE