

Needle roller bearing BTM1710-JTEKT - BTM1710-JTEKT

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/needle/btm1710-jtekt>

Drawn cup needle roller bearings Koyo



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min ⁻¹)		Bearing No. ²⁾	
F_w	D	C	b min.	C_0	C_{10}	Oil lub.		Caged type	
17	22	10	—	5.05	6.90	21 000		With open ends	With closed end

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (φ6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	16.989	17.000	21.972	21.993	8.2	—

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952470412
Inside diameter	17 mm
Inside diameter	0.669" inch
Outside diameter	22 mm
Outside diameter	0.866" inch
Thickness	10 mm
Thickness	0.394" inch
Weight	8.2 g
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE