

Needle roller bearing BHTM2510A-JTEKT - BHTM2510A-JTEKT

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/needle/bhtm2510a-jtekt>

Drawn cup needle roller bearings Koyo



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min ⁻¹)	Bearing No. ²⁾
F _w	D	C	b min.	C _r	C _{0r}	Oil lub.	Caged type With open ends With closed end
25	33	10	—	8.90	10.3	14 000	BHTM2510A

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (φ6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	24.987	25.000	32.989 ⁽¹⁾	33.014 ⁽¹⁾	18	—

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952471433
Inside diameter	25 mm
Outside diameter	33 mm
Thickness	10 mm
Weight	18 g
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE