

Needle roller bearing BHTM2525-JTEKT - BHTM2525-JTEKT

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/needle/bhtm2525-jtekt>

Drawn cup needle roller bearings Koyo



| Boundary dimensions (mm) | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | Bearing No. ²⁾ | |
|--------------------------|----|----|-------------------------|----------------|--------------------------------------|---------------------------|----------|
| F _w | D | C | b min. | C _r | C _{10r} | Oil lub. | |
| 25 | 33 | 25 | — | 24.5 | 40.6 | 14 000 | BHTM2525 |

| Full complement type | | Recommended dimensions (mm) | | | | (Refer.) Mass (g) | |
|----------------------|-----------------|-----------------------------|--------|-----------------------------|--------|-------------------|-----------------|
| With open ends | With closed end | Shaft dia. (φ6) min. | max. | Housing bore dia. (N7) min. | max. | With open ends | With closed end |
| — | — | 24.987 | 25.000 | 32.967 | 32.992 | 46 | — |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | JTEKT |
| N° Ean13 | 3663952471495 |
| Inside diameter | 25 mm |
| Outside diameter | 33 mm |
| Thickness | 25 mm |
| Weight | 46 g |
| Packaging | 1 |

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE