

## Needle roller bearing MHKM2530-JTEKT - MHKM2530-JTEKT

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/needle/mhkm2530-jtekt>

Drawn cup needle roller bearings Koyo



Boundary dimensions (mm)			Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	Bearing No. <sup>2)</sup>
$F_w$	$D$	$C$	$b$ min.	$C_0$	$C_{0r}$	Oil lub.
25	33	30	27.3	27.7	47.4	14 000
						Caged type With open ends    With closed end <b>MHKM2530</b>

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (φ6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	24.987	25.000	32.967	32.992	54	61

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952471525
Inside diameter	25 mm
Outside diameter	33 mm
Thickness	30 mm
Weight	61 g
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE