

## Needle roller bearing 30MKM3720-JTEKT - 30MKM3720-JTEKT

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/needle/30mkm3720-jtekt>

Drawn cup needle roller bearings Koyo



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	Bearing No. <sup>2)</sup>
$F_w$	$D$	$C$	$b$ min.	$C_r$	$C_{0r}$	Oil lub.	Caged type With open ends    With closed end
30	37	20	17.3	20.7	40.4	12 000	<b>30MKM3720</b>

Full complement type		Recommended dimensions (mm)				Refer. Mass (g)	
With open ends	With closed end	Shaft dia. (φ6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	29.987	30.000	36.967	36.992	40	45

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952471860
Inside diameter	30 mm
Inside diameter	1.181" inch
Outside diameter	37 mm
Outside diameter	1.457" inch
Thickness	20 mm
Thickness	0.787" inch
Weight	45 g
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE