


## Roller bearing NN3028K-JTEKT - NN3028K-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/roller/nn3028k-jtekt>

### Double-row cylindrical roller bearings Koyo



Boundary dimensions (mm)				Basic load ratings (kN)			Limiting speeds (min <sup>-1</sup> )		Bearing No.		
<i>d</i>	<i>D</i>	<i>B</i>	<i>r</i> min.	<i>F<sub>w</sub></i>	<i>E<sub>a</sub></i>	<i>C</i>	<i>C<sub>02</sub></i>	Grease lub.	Oil lub.	Cylindrical bore	Tapered bore
140	210	53	2	—	192	297	516	2 700	3 300	—	—
				Mounting dimensions (mm)				(Refer.) Mass (kg)			
Cylindrical bore		Tapered bore		<i>d<sub>a</sub></i> min.	<i>d<sub>a</sub></i> max.	<i>D<sub>a</sub></i> min.	<i>D<sub>a</sub></i> max.	<i>r<sub>a</sub></i> min.	<i>r<sub>a</sub></i> max.	Cylindrical bore	Tapered bore
				149	—	—	201	194	2	6.41	6.21

## PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952473185
Inside diameter	140 mm
Outside diameter	210 mm
Thickness	53 mm
Weight	6210 g
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE