


Tapered roller bearing 45244-JTEKT - 45244-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/45244-jtekt>

Double-row tapered roller bearings
TDI type Koyo



Boundary dimensions (mm)						Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
<i>d</i>	<i>D</i>	<i>B</i>	<i>T</i>	<i>r</i> max.	<i>r</i> min.	<i>C_r</i>	<i>C_{0r}</i>	Grease lub.	Oil lub.
220	340	90	90	3	4	805	1460	740	990

Bearing No.	Mounting dimensions (mm)						Con- stant <i>e</i>	Axial load factors			(Refer.) Mass (kg)
	<i>d_a</i> max.	<i>D_a</i> max.	<i>D_a</i> min.	<i>S_a</i> min.	<i>r_a</i> max.	<i>r_b</i> max.		<i>Y₂</i>	<i>Y₃</i>	<i>Y₀</i>	
45244	259	326	306	5	2.5	3	0.28	2.43	3.61	2.37	28.5

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952481937
Inside diameter	220 mm
Outside diameter	340 mm
Thickness	90 mm
Weight	28500 g
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE