

## Tapered roller bearing 45248-JTEKT - 45248-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/45248-jtekt>

Double-row tapered roller bearings — **Koyo**  
TDI type



Boundary dimensions (mm)						Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
d	D	B	T	r	r <sub>1</sub>	C <sub>r</sub>	C <sub>0r</sub>	Grease lub.	Oil lub.
240	360	92	92	3	4	915	1 790	690	920

  

Bearing No.	Mounting dimensions (mm)						Con- stant e	Axial load factors			(Refer.) Mass (kg)
	d <sub>a</sub> max.	D <sub>a</sub> max.	D <sub>a</sub> min.	S <sub>a</sub> min.	r <sub>a</sub> max.	r <sub>b</sub> max.		Y <sub>2</sub>	Y <sub>3</sub>	Y <sub>0</sub>	
45248	271	346	325	5	2.5	3	0.32	2.12	3.15	2.07	32.2

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952481968
Inside diameter	240 mm
Outside diameter	360 mm
Thickness	92 mm
Weight	32200 g
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE