

## Roller bearing NQ24-16-JTEKT - NQ24-16-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/roller/nq24-16-jtekt>

Machined ring needle roller bearings ————— **Koyo**  
F<sub>W</sub> 29 ~ 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)			Limiting speeds <sup>1)</sup> (min <sup>-1</sup> )		Bearing No.
F <sub>w</sub>	d	D	B	C <sub>r</sub>	C <sub>10</sub>	Oil lub.	Grease lub.	Without inner ring	
24	20	32	16	13.4	22.2	19 000	—	NQ24/16	
Mounting dimensions (mm)				[Refer.] Mass (kg)		[Refer.] Applicable inner ring No.			
With inner ring				Without inner ring	With inner ring				
	d <sub>1</sub>	D <sub>1</sub>	r <sub>1</sub>	0.035	0.052				
	max.	max.	max.						
	22	30	0.3						

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

## PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952482316
Inside diameter	24 mm
Outside diameter	32 mm
Thickness	16 mm
Weight	35 g
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE